Micro-THERM SVE Systems





EQUIPMENT FEATURES

Our **Micro-THERM** systems provide you with the most advanced and highest quality systems money can buy. Outstanding design means more run time, fewer site visits, and a huge reduction in operating costs. Our touchscreen operator panel contains all the information you need to perform any task, such as complete diagnostics and status, troubleshooting, electrical and PID displays, and system operational data.

Flow Range: 50 to 300 cfm, vacuums to 14" Hg

Small Footprint: Only 4-ft x 4ft, 1,400 lbs.

SVE Blower: The standard SVE Blower is rated for 220 cfm and vacuums to 14" Hg. Other blowers are also available, including 150 cfm dual phase water sealed pump to 28" Hg.

Burner System: Stainless steel *Jet-THERM* burner, max 380,000 btuh, 100:1 turndown ratio. 3-year warranty.

Dilution Air Blower: Enables dilution of extracted VOC's on the pressure side of the SVE blower. Optimize performance without losing well vacuum.

Stainless Water KO: 25-gallon water capacity with high level switch alarm shutoff.

OPTIONS

Catalyst Module
Water KO Auto-Pump
60% Heat Exchanger
Hi-Flow SVE Blower
370 cfm, to 15" Hg
Hi-Vac SVE Blower
120 cfm, to 20" Hg
Internet Access Telemetry .
Locking Enclosure
LEL & Oxygen Sensor
Open Trailer (5'x8' s-axle)



5310 Derry Ave, Unit C Agoura Hills, CA 91301-4509 (818) 706-2145 FAX (818) 706-2145